



EXTERIOR



INTERIOR

# ONE-WAY SMART GLASS

One-Way Smart Glass is developed using One-Way glass & standard smart glass with special technology.

TYPE	PRODUCT SIZES	SUITABLE USED FOR
Single Frame Type	4mm, 5mm, 6mm, 8mm, 10mm, 12mm	Privacy control observatory
Safety Type	5mm + 0.76pvb + 5mm	Bank, Police Station, Supermarket
Sound-Proof Type	5mm + 12A + 5mm	Special environment that requires sound proof
Blast-Resistant Type	5mm+1, 14pvb+12mm, 1.14pvb+5mm	Special environment that requires absolute safety


**FEATURES:**

- High Transparency
- Clarity Transparency
- Strong Reflection

**APPLICATIONS**

- Interrogation Room
- Psychiatric Ward
- University Lab
- Conference Hall
- Office
- Psychiatric Clini
- Observation
- Classroom
- Nuclear Plant
- Jail
- Army restricted area.c

TECHNICAL SPECIFICATIONS			
		Front	Rear
Glass Thickness		6mm	6mm
Transmittance	UV	2	2
	Visible Light	5	72
	Total Solar Energy	16	16
Reflectivity	Visible Light	87	10
	Total Solar Energy	30	6
U	Winter Night	10.9	10.9
	Summer Night	1.11	1.14
K	Winter Night	6.19	6.19
	Summer Night	6.28	6.28
Shielding Factor		0.93	0.93
Solar Thermal Energy Accumulation Coefficient		0.31	0.31



**Manufactured By:**

**CHIEFWAY OPTRONICS (MALAYSIA) SDN BHD**

Office: D-G-9 | Production & Showroom: D-G-8  
 Block D, Seri Gembira Avenue, No.6, Jalan Senang Ria,  
 Taman Gembira, 58200 Kuala Lumpur, Malaysia.

**Distributed By:**



www.therev.my

+6012-211 9625 • +6016-338 3813



www.avdisccovery.com.my



www.micro-zone.net

jeff-vikings • fredrick\_kam